Registered: May 14, 2009

Rvised: DecSeptember 13, 2012

Rvised: December 1, 2015

		TVISEd. December 1, 2016						
Certification number		MF-P004		Product Scope		otor driven Screw 150ZES(H), S(H)		
Registered company		ENOMOTO MACHINE CO., LTD.		Certified Product	150	ZES, 400ZES		
Criteria-based product(production)		120BF(April, 2002), 400ZFB(January, 2001)						
Requirements & environment factors		Evaluation item	Criteria	Evaluation result and/or remarks				
(1) Esse	ntial requirement		150ZESvs120BF 400ZESvs400Z		400ZESvs400ZFB			
Energy	Energy consumption	Reduction ratio	15% or more reduced	48%		37%		
saving				based on JFMA criteria				
(2) Selective requirement				150ZES vs 120BF		400ZES vs 400ZFB		
	Shrinkage of space/items	Number of air, hydraulic pressure parts	10% or more reduced	X		X		
Resources saving	Air	Total consumptin volume	10% or more reduced	X		X		
	Lubricating oil	Consumption Volume	10% or more reduced	X		X		
Minimum selective requirement		3items or more		3 items		3 items		
(3) Recommended requirement		Names of equipped devices/functions	Summary of effects on environmental burden reduction					
Ene dura disp of en emis	ergy saving, ability, long life, play/management environment info., ration/noise, ission omosphere, soil)	Adoption of V belt	Elimination of friction type ring belt enables less maintenance frequency and improvement of running cost.					
		Power regeneration capability	At the time of slide's speed reduction and reduction to stop operation, electric power is regenerated thanks to the power regeneration function.					
		Enery saving control	Each electrical component stops after a certain stop period.					
Environ		Lubrication oil supply to the screw parts	Oil supply to the screw parts is recycled for reduction of lubricating oil.					
		Constant supply of fixed volume of oil	Adoption of fixed supply valve enables the reduction of lubricating oil consumed.					
Minimum recommendation requirement		3 items or more	5 items					